

Block Up-Converter (BUC)

Ka-Band 40W



◆ Company Overview

RevGo designs and manufactures satellite earth station RF from low to high power. RevGo was founded in 2002 with its headquarters in the Washington DC corridor. RevGo's broad VSAT product line is produced to stringent quality standards using an ISO9001:2015 quality system:

- Block upconverter (BUC)
- Low noise block (LNB)
- Transceiver (Tx/Rx/OMT/filters)
- C-, Ku-, DBS-, Ka-bands
- 2 to 300W output power


◆ Reliability

- Highly integrated RF technologies (RFIC and GaN)
- Designed for high volume production
- Linearity optimized for high order modulation and high data rate
- Strict quality control processes resulting in <0.25% field failure rates

◆ Product Features

- Software selectable sub-band 27.5-31 GHz (single-, dual and tri-band)
- Independently removable fans without causing service interruption
- Variable power consumption 350W (@46dBm)
225W (@43dBm)
- Compact and light weight 12 lbs / 5.8 kg
- Low phase noise (exceeds IESS308/309)
- Stable linearity to 500 MHz bandwidth
- Independently removable fans
- Rugged design for extreme environments (-40 to +60°C)
- M&C with real-time clock, event log, web interface, SNMP, and O-BMIP

◆ Mechanical Diagram (Unit: inch (mm))



◆ Typical VSAT Applications

- Maritime
- 5G Backhaul
- SNG Vehicle
- Terminals
 - Fixed
 - Portable
 - Transportable

Block Up-Converter (BUC) Ka-Band 40W



SPECIFICATIONS

◆ RF Specifications

RF Frequency	General 27.5-31 GHz (Available in many band options)
IF Frequency	950-1950 MHz 950-1450 MHz 1000-2000 MHz
External Ref	10 MHz, 0 ± 5 dBm
Output Power	
Rated/Saturated	46 dBm
PLin¹	45 dBm
PLin²	44 dBm
PLin³	43 dBm
IMD3 (3dB from rated)	- 25 dBc
Small Signal Gain	70 dB
Gain Variation	1 dB p-p / 36 MHz 3 dB p-p / 500 MHz 4 dB p-p / 750 MHz
Gain stability	3 dB p-p
Gain Adjustment	20 dB (Step: 0.1 dB)
Phase Noise	-63 dBc / Hz @ 100 Hz -73 dBc / Hz @ 1 KHz -83 dBc / Hz @ 10 KHz -93 dBc / Hz @ 100 KHz
Output Spurious	-55 dBc

Notes:

- PLin¹**: -26 dBc regrowth, 1.5 SR (commercial satellite)
- PLin²**: -30 dBc regrowth, 1.0 SR (MIL-STD-188-164B, one-carrier)
- PLin³**: <-25 dBc IMD3 (MIL-STD-188-164B, two-carrier)

◆ Power Supply

Input Power	+36 to +56 V DC
Power Consumption	
@ PLin ³ Output	225W
@ Rated Output	350W

◆ Interfaces

RF Output Connector	WR28-G (Grooved)
RF Output VSWR	1.25:1
IF Connector	N-Type Female
IF Input VSWR	1.5:1
Power Connector	C01610C00600012
M&C Connector	RJ45 and optional PT02E-12-14P (RS485, RS232)
Alarm Status Indicator	LED (green/red)

◆ Physical Parameters

Size	(inches)	10.2*5.4*4.7
	(mm)	259*136*118
Weight	(lbs)	12 lbs
	(kg)	5.8 kg
Operating Temperature		-40 to +60°C
Humidity		0-100% (condensing)
Altitude		0-10,000 feet ASL

◆ Part Number / Ordering Information

RGUC – A <u>a</u> 40 – DC <u>b</u> <u>b</u> - M	
A: Frequency Band A = Ka-Band	7 = 27.5-30 GHz 8 = 28-30 GHz
a: Frequency Range 1 = 29-30 GHz 2 = 29.5-30 GHz 3 = 30-31 GHz 4 = 29-30 & 30-31 GHz 5 = 27.652-28.388 GHz 6 = 28.172-29.071 GHz	9 = 28.2-29 GHz 0 = 27.5-29 GHz T = 27.5-30 GHz
	bb = M&C Interface RE = RJ45 XX = RJ45 & RS485/232

◆ Contact Information

Website:	www.RevGoGroup.com	
Telephone:	+1 (703) 860-3522	
E-mail:	Sales@RevGoGroup.com	
Address:	12007 Sunrise Valley Dr., #450 Reston, VA 20191 USA	